



**<14 km**  
Range per Charge



**136 kg**  
Weight Capacity



**64.5 cm**  
Turning Radius



**GOCHAIR®**

## Experience Portability with the Go Chair®

The Go Chair® redefines portable mobility, combining lightweight travel and convenience with a sleek, bold design. Engineered with Pride's feather-touch technology, it disassembles easily into lightweight pieces, with the heaviest weighing just 16.3 kg. Designed for superior manoeuvrability, the Go Chair® features a compact 64.5 cm turning radius, making it effortless to navigate tight spaces. It also features convenient under-seat storage, keeping your personal items within reach. Available in two contemporary colours, it's time to get moving with the Go Chair®.





Feather -Touch Disassembly



Height and Width Adjustable Armrest



90° Swivel Seat with Under storage

RANGE PER CHARGE (MAX) <sup>1</sup>	Up to 14 km
MAXIMUM WEIGHT CAPACITY	136 kg
TURNING RADIUS	64.5 cm
MAXIMUM SPEED <sup>1</sup>	5.9 km/h
LENGTH & WIDTH <sup>2</sup>	L: 83.8 cm W: 57 cm
WEIGHT OF HEAVIEST PIECE	16.3 kg
GROUND CLEARANCE <sup>4</sup>	4.5 cm at frame
SEAT SIZE WIDTH & DEPTH	W: 45.7 cm x D: 43.1 cm (18" x 17")
STANDARD SEAT WEIGHT	13.6 kg (18" x 17")
SEAT-TO-FLOOR RANGE	46 cm - 51 cm

STANDARD ELECTRONICS	40A, PG GC3
DRIVE TRAIN	Two motor, rear-wheel drive
BRAKING SYSTEM	Regenerative and electro-mechanical
SUSPENSION TYPE	N/A
FRONT CASTORS	6" solid
DRIVE WHEELS	9" solid
REAR CASTORS	3" solid anti-tips
BATTERY REQUIREMENTS <sup>3</sup>	(2) 18 Ah, 12V
BATTERY CHARGER	Off-board, 2A
BATTERY WEIGHT	14 kg battery box
COLOUR OPTIONS	<input checked="" type="checkbox"/> Ruby Red <input type="checkbox"/> Pearl White

1. Varies with user weight, terrain type, battery amp hour (Ah), battery charge, battery condition and tyre condition.
2. Width of base (not including seat).
3. Deep cycle (AGM or gel cell type recommended)
4. Does not account for anti-tip clearance.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of 3%.